# Fuel-efficient design delivers bottom-line benefits.

Designed specifically for Less-Than-Truckload, Regional Distribution, and Vocational applications, the DD13<sup>™</sup> engine with BlueTec<sup>®</sup> emmisions technology delivers a smooth, quiet ride and up to 5% better fuel economy.\*

#### **Demand Economy**

- Smart, fuel-efficient design makes the most of every gallon
  - Get up to 5% better fuel economy\*
  - Pulls strong down to 1100 RPM so drivers can spend more time in top gear
  - Amplified Common Rail System (ACRS™) optimizes each injection event to minimize fuel consumption
  - Advanced cooling system allows for decreased fan on time minimizing fuel consumption

#### **Demand Serviceability**


- Lower your cost of ownership with easier serviceability
  - Longest scheduled maintenance intervals in its class
  - Oil, coolant and fuel filters are positioned above the frame rails for easier, faster and cleaner filter changes
  - Maintenance-free crankcase breather

## **Demand Performance**

- · Meet your deadline every time
  - Enjoy less shifting with an extremely wide and flat torque curve
  - Three-stage integrated Jacobs® engine brake offers quieter engine braking and provides superior braking horsepower for extended service brake life
  - Overall robust design provides B50 life of 1 million miles
  - Sturdy rear gear train and ribbed cast iron block minimize noise vibration harshness (NVH)
  - Wastegated asymmetrical turbocharger has fewer moving parts (compared with VGT design) for proven performance

## Demand BlueTec® Emissions Technology

- Proven BlueTec emissions technology meets EPA 2010 emissions requirements at the tailpipe
- Improves engine performance and fuel economy
- Simple to use, economical to own and time-tested experience
- Available with 1-Box<sup>™</sup> emissions package





Inline 6 Cylinder

17.3:1

781 cu. in. (12.8 L)

5.20 in. (132 mm)

6.15 in. (156 mm)

2540 lb. (1152 kg)

DDEC® 10

39.5 L

350-470

1250-1650

Optional

www.DetroitDiesel.com

Configuration

Displacement

Bore

Stroke

Weight (Dry)

Electronics

Oil Capacity


Torque Range

Horsepower Range

Rear-Engine Power Take-Off

Compression Ratio

### **Horsepower and Torque Curve**



#### **Power Ratings**

DD13 Engine Power Ratings				
370 HP @ 1800 RPM	1250 lb-ft @ 1100 RPM			
350 HP @ 1800 RPM	1350 lb-ft @ 1100 RPM			
380 HP @ 1800 RPM	1350 lb-ft @ 1100 RPM			
380 HP @ 1800 RPM	1450 lb-ft @ 1100 RPM			
410 HP @ 1800 RPM	1450 lb-ft @ 1100 RPM			
410 HP @ 1800 RPM	1550 lb-ft @ 1100 RPM			
435 HP @ 1800 RPM	1550 lb-ft @ 1100 RPM			
450 HP @ 1800 RPM	1550 lb-ft @ 1100 RPM			
410 HP @ 1800 RPM	1650 lb-ft @ 1100 RPM			
450 HP @ 1800 RPM	1650 lb-ft @ 1100 RPM			
470 HP @ 1800 RPM	1650 lb-ft @ 1100 RPM			

DD13 Engine Multi-Torque Power Ratings				
380 HP @ 1800 RPM	1350/1550 lb-ft @ 1100 RPM			
410 HP @ 1800 RPM	1450/1650 lb-ft @ 1100 RPM			

#### **Maintenance Intervals**

Item	Mi/Hr⁺	Severe-Duty	Short-Haul	Long-Haul		
Engine Oil and Filter Change*	Miles	25,000	35,000	50,000		
	Hours	640	895	1,280		
Fuel Filter Change	Miles	25,000	35,000	50,000		
	Hours	640	895	1,280		
Valve Lash Adjustment	Miles	Adjust at 100,000,	Adjust at 100,000, at 500,000 and then every 500,000 thereafter.			
	Hours	Adjust at 2,565,	Adjust at 2,565, at 12,825 and then every 12,825 thereafter.			
Diesel Particulate Filter	Miles	0 0	A "check engine light" will illuminate when ash requires removal. Normal DPF ash cleaning intervals are 300,000 to 400,000 miles.			
	Hours		A "check engine light" will illuminate when ash requires removal.  Normal DPF ash cleaning intervals are 9,000 to 10,250 hours.			
DEF Pump Filter	Miles	150,000	175,000	250,000		
	Hours	3,840	4,475	6,400		

<sup>\*</sup> Based on using Detroit Diesel's lube oil and oil analysis program. Severe-duty is up to 30,000 annual miles and a vehicle that averages less than 5 miles per gallon (mpg). Short-haul is between 30,000 and 60,000 annual miles and a vehicle that averages between 5.1 and 5.9 mpg. Long-haul is over 60,000 annual miles and a vehicle that averages greater than 6 mpg.

# **Standard Warranty**

Item -	Warranty Limits (Whichever Occurs First)		Repair Charge (Paid by Owner)		
	Months	Miles / Kilometers	Parts	Labor	
Engine	0-24	Unlimited	No charge	No charge	
Injectors	0-24	200,000 mi / 320,000 km	No charge	No charge	
Upon expiration of the 24-month warranty coverage, but within 500,000 mi / 800,000 km of use, the warranty continues to apply as follows:					
Major Components	25-60	500,000 mi / 800,000 km	No charge	Not covered	



For more information, call 1-800-445-1980. www.DetroitDiesel.com

ODC-EMC-FLY-0030-0210. Specifications are subject to change without notice. Detroit Diesel Corporation is registered to ISO 9001:2008. Copyright © Detroit Diesel Corporation.

All rights reserved. Detroit Diesel Corporation is a Daimler company.



<sup>†</sup> Miles/Hours, whichever occurs first.