

# DIESEL ENGINE-GENERATOR SET

## 250-JC6DT3

250 ekW / 60 Hz / Standby  
 220 ekW / 60 Hz / Prime  
 208 - 600V



### SYSTEM RATINGS

#### Standby

| Voltage (L-L)    | 208V**          | 240V**           | 480V**         | 600V**     |
|------------------|-----------------|------------------|----------------|------------|
| Phase            | 3               | 3                | 3              | 3          |
| PF               | 0.8             | 0.8              | 0.8            | 0.8        |
| Hz               | 60              | 60               | 60             | 60         |
| kW               | 250             | 250              | 250            | 250        |
| kVA              | 312.5           | 312.5            | 312.5          | 312.5      |
| AMPS             | 867             | 752              | 376            | 301        |
| skVA@30%         |                 |                  |                |            |
| Voltage Dip      | 520             | 520              | 700            | 722        |
| Generator Model* | 432CSL6210      | 432CSL6210       | 432CSL6210     | 432PSL6246 |
| Temp Rise        | 130°C/27°C      | 130°C/27°C       | 130°C/27°C     | 125°C/40°C |
| Connection       | 12 LEAD LOW WYE | 12 LEAD HI DELTA | 12 LEAD HI WYE | 4 LEAD WYE |


#### Prime

| Voltage (L-L)    | 208V**          | 240V**           | 480V**         | 600V**     |
|------------------|-----------------|------------------|----------------|------------|
| Phase            | 3               | 3                | 3              | 3          |
| PF               | 0.8             | 0.8              | 0.8            | 0.8        |
| Hz               | 60              | 60               | 60             | 60         |
| kW               | 220             | 220              | 220            | 220        |
| kVA              | 275             | 275              | 275            | 275        |
| AMPS             | 763             | 662              | 331            | 265        |
| skVA@30%         |                 |                  |                |            |
| Voltage Dip      | 520             | 520              | 700            | 722        |
| Generator Model* | 432CSL6210      | 432CSL6210       | 432CSL6210     | 432PSL6246 |
| Temp Rise        | 105°C/40°C      | 105°C/40°C       | 105°C/40°C     | 105°C/40°C |
| Connection       | 12 LEAD LOW WYE | 12 LEAD HI DELTA | 12 LEAD HI WYE | 4 LEAD WYE |

\* The Generator Model Number identified in the table is for standard C Series Configuration. Consult the factory for alternate configuration.

\*\* UL2200 Offered

## FACTS

- // EPA Tier 3 Certified
- // Engine-Generator Set Tested to ISO 8528-5 for Transient Response
- // UL2200, CSA Listing Offered
- // Accepts Rated Load in One Step Per NFPA 110, Level 1
- // All engine-generator sets are prototype and factory tested
- // MTU Onsite Energy is a single source supplier
- // Global Product Support
- // 2 Year Standard Warranty
- // Custom Design for Any Application
- // 6090HF485 Diesel Engine
  - 9.0 Liter Displacement
  - 4-Cycle
- // Complete Range of Accessories
- // Permanent Magnet Generator (PMG) - Optional
  - Brushless, Rotating Field
  - 300% Short Circuit Capability
  - 2/3 Pitch Windings
- // Digital Control Panel(s)
  - UL Recognized,  us, NFPA 110
  - Complete System Metering
  - LCD Display
- // Cooling System
  - Integral Set-Mounted
  - Engine Driven Fan

## STANDARD EQUIPMENT

### // Engine

Air Cleaners  
 Oil Pump  
 Full Flow Oil Filter  
 Jacket Water Pump  
 Thermostat  
 Exhaust Manifold - Dry  
 Blower Fan & Fan Drive  
 Radiator - Unit Mounted  
 Electric Starting Motor - 24V  
 Governor - Electric Isochronous  
 Base - Formed Steel  
 SAE Flywheel & Bell Housing  
 Charging Alternator - 24V  
 Battery Box & Cables  
 Flexible Fuel Connectors  
 Flexible Exhaust Connection  
 EPA Certified Engine

### // Generator

NEMA MG1, IEEE and ANSI standards compliance for temperature rise and motor starting  
 Sustained short circuit current of up to 300% of the rated current for up to 10 seconds  
 Self-Ventilated and Drip-Proof  
 Superior Voltage Waveform  
 Digital, Solid State, Volts-per-Hertz Regulator  
 No Load to Full Load Regulation

Brushless Alternator with Brushless Pilot Exciter  
 4 Pole, Rotating Field  
 130°C Standby Temperature Rise  
 1 Bearing, Sealed  
 Flexible Coupling  
 Full Amortisseur Windings  
 125% Rotor Balancing  
 3-Phase Voltage Sensing  
 ±1% Voltage Regulation  
 100% of Rated Load - One Step  
 3% Maximum Harmonic Content

### // Digital Control Panel(s)

Digital Metering  
 Engine Parameters  
 Generator Protection Functions  
 Engine Protection  
 SAE J1939 Engine ECU Communications  
 Windows-Based Software  
 Multilingual Capability  
 Remote Communications to our RDP-110 Remote Annunciator  
 16 Programmable Contact Inputs  
 7 Contact Outputs  
 UL Recognized,  us, CE Approved  
 Event Recording  
 IP 54 Front Panel Rating with Integrated Gasket  
 NFPA110 Level Compatible

## APPLICATION DATA

### // Engine

|                               |             |
|-------------------------------|-------------|
| Manufacturer                  | John Deere  |
| Model                         | 6090HF485   |
| Type                          | 4-Cycle     |
| Arrangement                   | 6-Inline    |
| Displacement: Cu In (lit)     | 548 (9)     |
| Bore: in (cm)                 | 4.66 (11.8) |
| Stroke: in (cm)               | 5.35 (13.6) |
| Compression Ratio             | 16:1        |
| Rated RPM                     | 1,800       |
| Engine Governor               | JDEC        |
| Max Power: Standby: bhp (kWm) | 422 (315)   |
| Max Power: Prime: bhp (kWm)   | 384 (287)   |
| Regulation                    | ± 25%       |
| Frequency                     | 60 Hz       |
| Air Cleaner                   | Dry         |

### // Liquid Capacity (Lubrication)

|   |              |
|---|--------------|
| Total Oil System: gal (lit)             | 10.6 (40)    |
| Engine Jacket Water Capacity: gal (lit) | 4.3 (16.2)   |
| System Coolant Capacity: gal (lit)      | 12.75 (48.3) |

### // Electrical

|  |       |
|--|-------|
| Electric Volts DC                      | 12    |
| Cold Cranking Amps Under 0°F (-17.8°C) | 1,100 |

### // Fuel System

|                                  |            |
|----------------------------------|------------|
| Fuel Supply Connection Size      | 1/2" NPT   |
| Fuel Return Connection Size      | 1/2" NPT   |
| Maximum Fuel Lift: ft (m)        | 6 (2)      |
| Recommended Fuel                 | Diesel #2  |
| Total Fuel Flow: gal/hr (lit/hr) | 63.4 (240) |

### // Fuel Consumption

|  | STANDBY     | PRIME       |
|--|-------------|-------------|
| At 100% of Power Rating: gal/hr (lit/hr) | 18 (68.2)   | 16.2 (61.3) |
| At 75% of Power Rating: gal/hr (lit/hr)  | 13.6 (51.5) | 12.3 (46.6) |
| At 50% of Power Rating: gal/hr (lit/hr)  | 9.2 (34.8)  | 8.4 (31.8)  |

### // Cooling - Radiator System

|   | STANDBY      | PRIME        |
|---|--------------|--------------|
| Ambient Capacity of Radiator: °F (°C)   | 122 (50)     | 122 (50)     |
| Max. Restriction of Cooling Air, Intake, and Discharge Side of Rad.: in. H <sub>2</sub> O (kPa) | 0.5 (0.12)   | 0.5 (0.12)   |
| Water Pump Capacity: gpm (lit/min)  | 74 (280)     | 74 (280)     |
| Heat Rejection to Coolant: BTUM (kW)  | 7,001 (123)  | 6,887 (121)  |
| Heat Rejection to Air to Air: BTUM (kW)   | 4,309 (76)   | 4,229 (74)   |
| Heat Radiated to Ambient: BTUM (kW)   | 1,739 (30.6) | 1,489 (26.2) |

### // Air Requirements


|  | STANDBY      | PRIME        |
|--|--------------|--------------|
| Aspirating: *SCFM (m <sup>3</sup> /min)  | 802 (22.7)   | 778 (22)     |
| Air Flow Required for Rad. Cooled Unit: *SCFM (m <sup>3</sup> /min)                              | 23,247 (658) | 23,247 (658) |
| Air Flow Required for Heat Exchanger/Remote Rad. based on 25°F Rise: *SCFM (m <sup>3</sup> /min) | 3,922 (112)  | 3,359 (96)   |

\* Air density = 0.0739 lbm/ft<sup>3</sup> (1.184 kg/m<sup>3</sup>)

### // Exhaust System

|   | STANDBY    | PRIME      |
|---|------------|------------|
| Gas Temp. (Stack): °F (°C)                                  | 882 (475)  | 795 (424)  |
| Gas Volume at Stack Temp: CFM (m <sup>3</sup> /min)         | 1,930 (55) | 1,769 (50) |
| Maximum Allowable Back Pressure: in. H <sub>2</sub> O (kPa) | 40 (10)    | 40 (10)    |

## WEIGHTS AND DIMENSIONS



Drawing above for illustration purposes only, based on standard open power 480 volt generator. Lengths may vary with other voltages. Do not use for installation design.

| System | Dimensions (L x W x H)                        | Weight (less tank)  |
|--------|---|---------------------|
| OPU    | 120 x 48 x 68.4 in (3,050 x 1,220 x 1,740 mm) | 4,886 lb (2,216 kg) |

Weights and dimensions are based on open power units and are estimates only. Consult the factory for accurate weights and dimensions for your specific generator set.

## SOUND DATA

| Unit Type                          | Standby Full Load | Standby No Load | Prime Full Load | Prime No Load |
|------------------------------------|-------------------|-----------------|-----------------|---------------|
| OPU w/Critical Grade Muffler (dBA) | 94                | 87              | 92.5            | 87            |
| Sound Attenuated Enclosure (dBA)   | 86                | 79              | 84.5            | 79            |

Measurements for sound data are taken at 23 ft (7 m).

## EMISSIONS DATA

|                              |           |           |
|------------------------------|-----------|-----------|
| <b>NO<sub>x</sub> + NMHC</b> | <b>CO</b> | <b>PM</b> |
| 2.76                         | 0.43      | 0.064     |

### All units are in g/hp-hr and are EPA D2 cycle values.

Emission levels of the engine may vary as a function of ambient temperature, barometric pressure, humidity, fuel type and quality, installation parameters, measuring instrumentation, etc. The data provided are laboratory results from one engine representing this rating. The data was obtained under controlled environmental conditions with calibrated instrumentation traceable to the United States National Bureau of Standards and in compliance with US EPA regulations found within 40 CFR Part 89. The weighted cycle value from each engine is guaranteed to be below the US EPA Standards at the US EPA defined conditions.

## RATING DEFINITIONS AND CONDITIONS

- // Ambient capability factor at 984 ft (300 m). Consult your local MTU Onsite Energy Power Generation Distributor for other altitudes.
- // Standby ratings apply to installations served by a reliable utility source. The standby rating is applicable to varying loads for the duration of a power outage. No overload capability for this rating. Ratings are in accordance with ISO-3046/1, BS 5514, AS 2789, and DIN 6271.
- // Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Ratings are in accordance with ISO-8528/1, overload power in accordance with ISO-3046/1, BS 5514, AS 2789, and DIN 6271. For limited running time and base load ratings, consult the factory.
- // Deration Factor:
  - Altitude:** 5% per 1,000 ft (305 m) above 8,900 ft (2,700 m).
  - Temperature:** 0.5% per 10°F (5.5°C) above 77°F (25°C).

Materials and specifications subject to change without notice.

# DIESEL ENGINE-GENERATOR SET

## 250-XC6DT3

250 ekW / 60 Hz / Standby  
 220 ekW / 60 Hz / Prime  
 208 - 600V



### SYSTEM RATINGS

#### Standby

| Voltage (L-L)    | 240V**          | 208V**          | 240V**           | 480V**         | 600V**     |
|------------------|-----------------|-----------------|------------------|----------------|------------|
| Phase            | 1               | 3               | 3                | 3              | 3          |
| PF               | 1.0             | 0.8             | 0.8              | 0.8            | 0.8        |
| Hz               | 60              | 60              | 60               | 60             | 60         |
| kW               | 250             | 250             | 250              | 250            | 250        |
| kVA              | 250             | 312.5           | 312.5            | 312.5          | 312.5      |
| AMPS             | 1042            | 867             | 752              | 376            | 301        |
| skVA@30%         |                 |                 |                  |                |            |
| Voltage Dip      | 450             | 520             | 520              | 700            | 720        |
| Generator Model* | 572RSL4025      | 432CSL6210      | 432CSL6210       | 432CSL6210     | 432PSL6246 |
| Temp Rise        | 130°C/27°C      | 130°C/27°C      | 130°C/27°C       | 130°C/27°C     | 125°C/40°C |
| Connection       | 12 LEAD ZIG-ZAG | 12 LEAD LOW WYE | 12 LEAD HI DELTA | 12 LEAD HI WYE | 4 LEAD WYE |


#### Prime

| Voltage (L-L)    | 240V            | 208V            | 240V             | 480V           | 600V       |
|------------------|-----------------|-----------------|------------------|----------------|------------|
| Phase            | 1               | 3               | 3                | 3              | 3          |
| PF               | 1.0             | 0.8             | 0.8              | 0.8            | 0.8        |
| Hz               | 60              | 60              | 60               | 60             | 60         |
| kW               | 220             | 220             | 220              | 220            | 220        |
| kVA              | 275             | 275             | 275              | 275            | 275        |
| AMPS             | 917             | 763             | 662              | 331            | 265        |
| skVA@30%         |                 |                 |                  |                |            |
| Voltage Dip      | 450             | 520             | 520              | 700            | 720        |
| Generator Model* | 572RSL4025      | 432CSL6210      | 432CSL6210       | 432CSL6210     | 432PSL6246 |
| Temp Rise        | 105°C/40°C      | 105°C/40°C      | 105°C/40°C       | 105°C/40°C     | 105°C/40°C |
| Connection       | 12 LEAD ZIG-ZAG | 12 LEAD LOW WYE | 12 LEAD HI DELTA | 12 LEAD HI WYE | 4 LEAD WYE |

\* The Generator Model Number identified in the table is for standard C Series Configuration. Consult the factory for alternate configuration.

\*\* UL2200 Offered

## FACTS

- // EPA Tier 3 Certified
- // Engine-Generator Set Tested to ISO 8528-5 for Transient Response
- // UL2200, CSA Listing Offered
- // Accepts Rated Load in One Step Per NFPA 110, Level 1
- // All engine-generator sets are prototype and factory tested
- // MTU Onsite Energy is a single source supplier
- // Global Product Support
- // 2 Year Standard Warranty
- // Custom Design for Any Application
- // Series 60 (6063HV35) Diesel Engine
  - 14.0 Liter Displacement
  - Electronic Unit Pump Injection
- 4-Cycle
- // Complete Range of Accessories
- // Permanent Magnet Generator (PMG) - Optional
  - Brushless, Rotating Field
  - 300% Short Circuit Capability
  - 2/3 Pitch Windings
- // Digital Control Panel(s)
  - UL Recognized,  us, NFPA 110
  - Complete System Metering
  - LCD Display
- // Cooling System
  - Integral Set-Mounted
  - Engine Driven Fan

## STANDARD EQUIPMENT

### // Engine

Air Cleaners  
 Oil Pump  
 Full Flow Oil Filter  
 Jacket Water Pump  
 Thermostat  
 Exhaust Manifold - Dry  
 Blower Fan & Fan Drive  
 Radiator - Unit Mounted  
 Electric Starting Motor - 24V  
 Governor - Electric Isochronous  
 Base - Formed Steel  
 SAE Flywheel & Bell Housing  
 Charging Alternator - 24V  
 Battery Box & Cables  
 Flexible Fuel Connectors  
 Flexible Exhaust Connection  
 EPA Certified Engine

### // Generator

NEMA MG1, IEEE and ANSI standards compliance for temperature rise and motor starting  
 Sustained short circuit current of up to 300% of the rated current for up to 10 seconds  
 Self-Ventilated and Drip-Proof  
 Superior Voltage Waveform  
 Digital, Solid State, Volts-per-Hertz Regulator  
 No Load to Full Load Regulation

Brushless Alternator with Brushless Pilot Exciter  
 4 Pole, Rotating Field  
 130°C Standby Temperature Rise  
 1 Bearing, Sealed  
 Flexible Coupling  
 Full Amortisseur Windings  
 125% Rotor Balancing  
 3-Phase Voltage Sensing  
 ±1% Voltage Regulation  
 100% of Rated Load - One Step  
 3% Maximum Harmonic Content

### // Digital Control Panel(s)

Digital Metering  
 Engine Parameters  
 Generator Protection Functions  
 Engine Protection  
 SAE J1939 Engine ECU Communications  
 Windows-Based Software  
 Multilingual Capability  
 Remote Communications to our RDP-110 Remote Annunciator  
 16 Programmable Contact Inputs  
 7 Contact Outputs  
 UL Recognized,  us, CE Approved  
 Event Recording  
 IP 54 Front Panel Rating with Integrated Gasket  
 NFPA110 Level Compatible

## APPLICATION DATA

### // Engine

|                               |                         |
|-------------------------------|-------------------------|
| Manufacturer                  | MTU Detroit Diesel      |
| Model                         | Series 60<br>(6063HV35) |
| Type                          | 4-Cycle                 |
| Arrangement                   | 6-Inline                |
| Displacement: Cu In (lit)     | 855 (14)                |
| Bore: in (cm)                 | 5.24 (13.3)             |
| Stroke: in (cm)               | 6.61 (16.8)             |
| Compression Ratio             | 16:1                    |
| Rated RPM                     | 1,800                   |
| Engine Governor               | DDEC                    |
| Max Power: Standby: bhp (kWm) | 490 (366)               |
| Max Power: Prime: bhp (kWm)   | 424 (316)               |
| Regulation                    | ± 25%                   |
| Frequency                     | 60 Hz                   |
| Air Cleaner                   | Dry                     |

### // Liquid Capacity (Lubrication)

|   |          |
|---|----------|
| Total Oil System: gal (lit)             | 9.5 (36) |
| Engine Jacket Water Capacity: gal (lit) | 6 (23)   |
| System Coolant Capacity: gal (lit)      | 42 (159) |

### // Electrical

|  |     |
|--|-----|
| Electric Volts DC                      | 24  |
| Cold Cranking Amps Under 0°F (-17.8°C) | 950 |

### // Fuel System

|                                  |            |
|----------------------------------|------------|
| Fuel Supply Connection Size      | 1/2" NPT   |
| Fuel Return Connection Size      | 1/2" NPT   |
| Maximum Fuel Lift: ft (m)        | 6.7 (2.1)  |
| Recommended Fuel                 | Diesel #2  |
| Total Fuel Flow: gal/hr (lit/hr) | 86.9 (329) |

### // Fuel Consumption

|  | STANDBY   | PRIME     |
|--|-----------|-----------|
| At 100% of Power Rating: gal/hr (lit/hr) | 20.1 (76) | 16.8 (64) |
| At 75% of Power Rating: gal/hr (lit/hr)  | 15.3 (58) | 13.2 (50) |
| At 50% of Power Rating: gal/hr (lit/hr)  | 10.5 (40) | 8.3 (31)  |

### // Cooling - Radiator System

|   | STANDBY      | PRIME       |
|---|--------------|-------------|
| Ambient Capacity of Radiator: °F (°C)   | 122 (50)     | 122 (50)    |
| Max. Restriction of Cooling Air, Intake, and Discharge Side of Rad.: in. H <sub>2</sub> O (kPa) | 0.5 (0.12)   | 0.5 (0.12)  |
| Water Pump Capacity: gpm (lit/min)  | 96 (363)     | 96 (363)    |
| Heat Rejection to Coolant: BTUM (kW)  | 7,950 (140)  | 7,000 (123) |
| Heat Rejection to Air to Air: BTUM (kW)   | 5,150 (90)   | 4,750 (83)  |
| Heat Radiated to Ambient: BTUM (kW)   | 4,908 (86.3) | 4,723 (83)  |

### // Air Requirements


|  | STANDBY      | PRIME        |
|--|--------------|--------------|
| Aspirating: *SCFM (m <sup>3</sup> /min)  | 1,105 (31)   | 1,070 (30)   |
| Air Flow Required for Rad.<br>Cooled Unit: *SCFM (m <sup>3</sup> /min)                                 | 18,891 (535) | 18,891 (535) |
| Air Flow Required for Heat<br>Exchanger/Remote Rad. based<br>on 25°F Rise: *SCFM (m <sup>3</sup> /min) | 11,070 (315) | 10,651 (303) |

\* Air density = 0.0739 lbm/ft<sup>3</sup> (1.184 kg/m<sup>3</sup>)

### // Exhaust System

|  | STANDBY      | PRIME        |
|--|--------------|--------------|
| Gas Temp. (Stack): °F (°C)                                     | 944 (507)    | 871 (466)    |
| Gas Volume at Stack<br>Temp: CFM (m <sup>3</sup> /min)         | 2,903 (82)   | 2,657 (75)   |
| Maximum Allowable<br>Back Pressure: in. H <sub>2</sub> O (kPa) | 40.8 (10.16) | 40.8 (10.16) |

## WEIGHTS AND DIMENSIONS



Drawing above for illustration purposes only, based on standard open power 480 volt generator. Lengths may vary with other voltages. Do not use for installation design.

### System

OPU

### Dimensions (L x W x H)

140 x 57 x 79.6 in (3,560 x 1,450 x 2,020 mm)

### Weight (less tank)

5,841 lb (2,649 kg)

Weights and dimensions are based on open power units and are estimates only. Consult the factory for accurate weights and dimensions for your specific generator set.

## SOUND DATA

| Unit Type                          | Standby Full Load | Standby No Load | Prime Full Load | Prime No Load |
|------------------------------------|-------------------|-----------------|-----------------|---------------|
| OPU w/Critical Grade Muffler (dBA) | 94                | 87              | 92.5            | 87            |
| Sound Attenuated Enclosure (dBA)   | 86                | 79              | 84.5            | 79            |

Measurements for sound data are taken at 23 ft (7 m).

## EMISSIONS DATA

|                              |           |           |
|------------------------------|-----------|-----------|
| <b>NO<sub>x</sub> + NMHC</b> | <b>CO</b> | <b>PM</b> |
| 2.74                         | 0.56      | 0.09      |

### All units are in g/hp-hr and are EPA D2 cycle values.

Emission levels of the engine may vary as a function of ambient temperature, barometric pressure, humidity, fuel type and quality, installation parameters, measuring instrumentation, etc. The data provided are laboratory results from one engine representing this rating. The data was obtained under controlled environmental conditions with calibrated instrumentation traceable to the United States National Bureau of Standards and in compliance with US EPA regulations found within 40 CFR Part 89. The weighted cycle value from each engine is guaranteed to be below the US EPA Standards at the US EPA defined conditions.

## RATING DEFINITIONS AND CONDITIONS

- // Ambient capability factor at 984 ft (300 m). Consult your local MTU Onsite Energy Power Generation Distributor for other altitudes.
- // Standby ratings apply to installations served by a reliable utility source. The standby rating is applicable to varying loads for the duration of a power outage. No overload capability for this rating. Ratings are in accordance with ISO-3046/1, BS 5514, AS 2789, and DIN 6271.
- // Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Ratings are in accordance with ISO-8528/1, overload power in accordance with ISO-3046/1, BS 5514, AS 2789, and DIN 6271. For limited running time and base load ratings, consult the factory.
- // Deration Factor:
  - Altitude:** 1% per 1,000 ft (305 m) above 600 ft (183 m).
  - Temperature:** 1% per 10°F (5.5°C) above 77°F (25°C).

Materials and specifications subject to change without notice.